





FEATURES

- Long-life 10+ year average sensor life
- Two-alarm setpoints for 19.5% and 18.0%
- 3 Year warranty
- Digital display and 4-20mA analog output
- · Wall mounting brackets
- Built-in flow sample pump
- UL, C UL, and CE approvals
- · International power supply included

Sample Draw Oxygen Monitor with 10+ Year Sensor

ITEM #: TX-1100SAM (99130)

Product Summary

The Sample Draw Oxygen Deficiency Monitor is perfect for storage areas, confined spaces, and other locations where remote oxygen monitoring is required. The built-in pump samples oxygen levels up to 100 ft away and is suitable for facilities that use inert gases including, but not limited to, nitrogen, helium, and argon. The monitor is ideal for environments such as MRI facilities, cryogenic spas, hospitals, freezers, and laboratories. The monitor will remain accurate at temperatures as low as -40C. PureAire's durable, non-depleting, zirconium oxide sensor will last up to 10+ years in a normal environment, without needing to be replaced.

Facilities That Need This Product

- MRI Rooms
- Hospitals
- Pharmaceutical Manufacturers
- Laboratories

Why choose PureAire?

PureAire Monitoring Systems, Inc. is a leader in oxygen monitoring and gas detection. For over 20 years, we have dedicated ourselves to the safety of our clients, and the customers they serve, by manufacturing monitors that are long-lasting, accurate, and reliable. PureAire takes pride in providing exceptional customer service, along with 24/7 availability to our technical service department.

Why a Sample Draw O2 Deficiency Monitor?

The Sample Draw O2 Deficiency Monitor is designed for continuous remote monitoring in locations where it is not possible to place the monitor, such as MRI rooms, and where low oxygen levels pose a hazard to personnel.

What gases can be detected with a Sample Draw O2 Deficiency Monitor?

PureAire's Sample Draw O2 Deficiency Monitor can be used to measure oxygen levels in an ambient atmosphere where inert gases, including nitrogen, helium, argon, and carbon dioxide are used.

Easy to Use

Secure the monitor to the wall so that the display is visible, connect a length of sample tube, up to 100 feet, and plug in the monitor. The monitor will begin sampling oxygen levels after a brief startup period. Oxygen levels are displayed clearly on the screen for easy access and visibility.

* Sampling tubes can be used in various locations including MRI Rooms

Top Advantages of Sample Draw Oxygen Monitor




Oxygen Deficiency Alarm


PureAire's O2 Monitor comes with 2 adjustable alarm setpoints that can connect to a horn/strobe, exhaust fan, 8 channel controller, remote display, or into building systems. Alarm signals also can tie into automatic shut-off valves when oxygen levels fall below the OSHA threshold.




Easy To Use

The Air Check O2 Deficiency Monitor provides constant monitoring with little to no adjustments, saving you time and money while allowing the monitor to operate seamlessly. Our quality sensor makes this the longest lasting O2 monitor on the market.







Top Accessories



8 Channel Programmable Controller for O2 or Gas Monitors



Remote Digital Display



Red Horn/Strobe 24VDC

ITEM #: 99058

ITEM #: 99091

ITEM #: 42002



00 44 16 98 90 72 60

mtlgas@bwteq.com www.bwteq.com

BW Technology, Ltd Grovewood Business Centre Wren Court Strathclyde Business Park Bellshill ML4 3NQ UK